

TRINITY Live & Stabilized Remote Head - Upgrade Sets Options



Configuration Overview | 8.0.1 / 2024.10

TRINITY 1 -> TRINITY Live - Upgrade Sets Options

TRINITY 1 to TRINITY 2: no upgrade available

TRINITY 1

not sold anymore

OPTION

TRINITY 1, 24V

24V Upgrade for TRINITY Gen. 1, [KK.0024710](#)

TRINITY Live Upgrade Set Basic, [KK.0044512](#)

Variant 1:

An Owner Operator wants to upgrade his own system to TRINITY Live. In this case, the Owner Operator contacts the ARRI Service in his region. It can then be decided on site whether the conversion will be carried out locally or at ARRI Service in Munich. The conversion takes two days, including all necessary tests and, if necessary, additional time for shipping.

Variant 2:

An operator who wanted to buy a TRINITY Live was offered a used TRINITY Gen. 1 by another owner. In this case, ARRI Service offers you a pre-check for the device to be sold. This way, the new customer can be sure that the purchase of the used system is worthwhile and that the conversion to TRINITY Live is feasible. Tools and the necessary training are available to the service staff in the regions from Q1 2024 for this pre-check.
Plus possible costs for other necessary ARRI services.

24V Upgrade for TRINITY Live (Gen.1), [KK.0050214](#)

Variant 1 and 2 plus possible costs for other necessary ARRI services.
This 24 V upgrade for TRINITY Live allows the system to provide reliable 24 V camera power when operators need to fly an ALEXA Mini LF, ALEXA 35, or Sony Venice. TRINITY Gen.1 rigs previously upgraded to 24 V must still be fitted with this new 24 V upgrade

Master Grip TRINITY 1 Pro Set, [KK.0049712](#)

If this function is to be part of a TRINITY Live upgrade, it must be ordered at the same time as the actual upgrade. This is the only way to avoid unnecessary costs.
This upgrade gives operators simultaneous control of a zoom lens and the stabilizer's tilt axis via a common LBUS controller. The Zoom will be controlled by the LCUBE CUB-2 or by a c-force mini motor.

Required Accessory Sets

Tally Set for TRINITY Gen.1, 3pin Lemo, [KK.0044682](#)

The TALLY Gen.2 is required to integrate the TRINITY Live into any Multicam application.

CCP Live Camera Control Panel Live Set, [KK.0047755](#)

The CCP Live is based on the CCP-1 and has been expanded to include an HDMI down converter, an HD SDI video out socket and a Tally out socket. This allows the operator to get a direct monitor video feed from the camera even when both video outputs are used for 2 x 6G video. The additional 1080 HD SDI video signal allows a control monitor to be connected to the camera if both video out sockets are already in use. If the camera is integrated into a multi-cam setup, the Tally Gen. 2 system can be controlled via the Tally Out socket.

TRINITY Live

sold only via CPO

Stabilized Remote Head - Upgrade Sets Options

Only the following upgrade paths are currently available

SRH-360

not sold anymore

360 EVO Upgrade for SRH-360, [KK.0050638](#)

UPGRADE

EVO-360

360 EVO Basic Set, No Joystick
[KK.0050103](#)

SRH-3

not sold anymore

360 EVO Upgrade for SRH-3, [KK.0050639](#)

UPGRADE